(71) 出願人（米国を除くすべての指定国について）
協和醱酵工業株式会社
(KYOWA HAKKO KOGYO CO., LTD.)[JP/JP]
〒100-8185　東京都千代田区大手町一丁目6番1号　Tokyo, (JP)
(72) 発明者；および
(75) 発明者／出願人（米国についてのみ）
渡邊　靖(WATANABE, Yasushi)[JP/JP]
森本　清(MORIMOTO, Kiyoshi)[JP/JP]
岩瀬雄司(IWASE, Yuji)[JP/JP]
〒411-8731　静岡県駿東郡長泉町下土狩1188
協和醱酵工業株式会社　富士工場内　Shizuoka, (JP)
(74) 代理人
弁理士　中井宏行(NAKAI, Hiroyuki)
〒665-0845　兵庫県宝塚市栄町2丁目2番1号
ソリオ3 2階　Hyogo, (JP)

(54)Title:　**TABLETS AND PROCESS FOR PRODUCING TABLETS**

(54)発明の名称　　錠剤、及び錠剤の製造方法

(57) Abstract

Tablets containing a drug affected in contact with a lubricating agent, wherein the tablets contain no lubricating agent in it, the inner structure of the tablets comprises a compressed mixture of the drug with a filler, and a lubricating agent is located on the tablet surface. A process for producing tablets which involves the step of mixing a drug affected in contact with a lubricating agent with a filler to give a mixture; the step of mixing a lubricating agent powder and dispersing with air-pulsating wave under positive pressure; the step of spraying the lubricating agent powder, which has been dispersed by the above air-pulsating wave under positive pressure, onto the bottom face of the upper pestle, the top face of the lower pestle and the side face of the mortar of a tabletting machine so as to coat the bottom face of the upper pestle, the top face of the lower pestle and the side face of the mortar with the powder; and the step of compression-molding the above mixture by using the pestles and mortar coated at each surface with the lubricating agent.